


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	10/12/2016	SM	JAG




ASSY QTY	ASSY QTY	ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			X		-1	1	HOIST ASSEMBLY			2
		X	1		-3		WELDMENT 1			3
		1			-5	1	HORIZONTAL BEAM 1	STEEL TUBE		4
		1			-7	1	HORIZONTAL BEAM 2	STEEL TUBE		5
		2			-9	2	VERTICAL BEAM 1	STEEL TUBE		6
		4			-11	4	BRACE 1	A36/1018/1020 HR		7
		1			-13	1	PLATE	A36/1018/1020 HR		8
		2			-15	2	BRACE 2	A36/1018/1020 HR		9
	X				-17	2	CLAMP ASSEMBLY			10
X	1				-19	2	WELDMENT 2			11
1					-21	1	CLAMP BEAM 1	A36/1018/1020 HR		12
1					-23	1	VERTICAL BEAM 2	STEEL TUBE		13
2					-25	2	BRACE 3	A36/1018/1020 HR		14
	1				-27	2	CLAMP BEAM 2	A36/1018/1020 HR		15
	1				-29	2	ADJUSTABLE BUMPER	6061		16
	1				-31	2	SWING BOLT	SS 303		17
	1				-33	2	PAD 1	C200	(I.R. SPECIALTY)	18
	1				-35	2	PAD 2	C200	(I.R. SPECIALTY)	19
	1				-37	2	KNOB	ALUMINUM	THREADED KNOB (MCMaster-CARR # 62015K212) MODIFIED	20
	2			B/O	-39	4	SOCKET CAP SCREW	SS	M6 X 1.0 X 16MM (MCMaster-CARR # 91292A135)	10
	2			B/O	-41	4	HEX HEAD CAP SCREW	STEEL	M8 X 1.25 X 50MM (MCMaster-CARR # 91280A546)	10
	4			B/O	-43	8	WASHER	STEEL	M8 (MCMaster-CARR # 91166A270)	10
	2			B/O	-45	4	LOCKNUT	STEEL	M6 X 1.25 (MCMaster-CARR # 90576A117)	10
	1			B/O	-47	2	SPRING PIN	SS	Ø3MM (MCMaster-CARR # 91610A408)	10
		3	B/O	-49			THIN HEX NUT	STEEL	M16 X 2 (MCMaster-CARR # 90695A125)	2
		3	B/O	-51			WASHER	STEEL	M16 (MCMaster-CARR # 91166A310)	2
		3	B/O	-53			HOIST RING	STEEL	RUD # VWBG-V 1.3M16 (GRAINGER # 16A740)	2
		2	B/O	-55			BALL LOCK PIN	SS	M10 X 65 MM (MCMaster-CARR # 93680A375)	2
		2	B/O	-57			LANYARD	SS	Ø IN. (MCMaster-CARR # 30345T547)	2
		2	B/O	-59			DRIVE SCREW	STEEL	.18 IN. SHANK X 3/8 IN LONG (MCMaster-CARR # 90081A240)	2
ASSY -19	ASSY -17	ASSY -3	ASSY -1							

- NOTES:  
1. REF. AIRBUS T/N: M259V1000102.  
2. LOAD TEST TO 435 Kg (960 LBS).

DART AEROSPACE			
TITLE RESCUE HOIST SLING			
DWG NO. RBEM259V1000102			REV 1
MAT'L HEAT TREAT FINISH SPEC		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125/	
DRAWN BY: MACKOVJAK		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: CLOUGH		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USED ON MODEL	
APPROVED: GILBERT		H175	
SCALE 1:8		DATE 5/27/2016	SHEET 1 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED








(-1)  
HOIST ASSEMBLY

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-1</b>	REV <b>1</b>
MAT'L REPT TREAT FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125°
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
DRAWN BY: <b>MACKOVJAK</b>	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
CHECKED: <b>CLOUGH</b>	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
OPPS APPR: <b>ANDERSON</b>	USED ON MODEL
QA APPR: <b>LINDSAY</b>	<b>H175</b>
APPROVED: <b>GILBERT</b>	
SCALE <b>1:8</b>	DATE <b>5/27/2016</b>
SHEET 2 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.




REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED



DART AEROSPACE			
TITLE RESCUE HOIST SLING			
DWG NO. RBEM259V1000102-3			REV 1
MAT'L HEAT TREAT FINISH POWDER COAT YELLOW SPEC FED #13538		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125/	
DRAWN BY: MACKOVJAK		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: CLOUGH		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USED ON MODEL H175	
APPROVED: GILBERT		SCALE 1:12 DATE 5/27/2016 SHEET 3 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-5)

HORIZONTAL BEAM 1

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-5</b>	REV <b>1</b>
MAT'L STEEL TUBE	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -3	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125/✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:4	DATE 5/27/2016
	SHEET 4 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-7)

HORIZONTAL BEAM 2

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-7</b>	REV <b>1</b>
MAT'L STEEL TUBE	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -3	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125/✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:4	DATE 5/27/2016
	SHEET 5 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



(-9)




VERTICAL BEAM 1

<b>DART</b> AEROSPACE	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-9</b>	REV <b>1</b>
MAT'L STEEL TUBE	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -3	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:4	DATE 5/27/2016
	SHEET 6 OF 20



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(11)

BRACE 1

<b>DART</b> AEROSPACE	
TITLE RESCUE HOIST SLING	
DWG NO. RBEM259V1000102-11	REV 1
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -3	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
SCALE 1:2	USED ON MODEL
DATE 5/27/2016	H175
	SHEET 7 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-13)  
PLATE

<b>DART</b> AEROSPACE	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-13</b>	REV <b>1</b>
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -3	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:4	DATE 5/27/2016
	SHEET 8 OF 20



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
APPROVED				




(15)

BRACE 2


<b>DART</b> AEROSPACE	
TITLE RESCUE HOIST SLING	
DWG NO. RBEM259V1000102-15	REV 1
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -1	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
SCALE 1:1	DATE 5/27/2016
	SHEET 9 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	



CLAMP ASSEMBLY






NOTES:  
1. ATTACH -33 TO -21 AND -35 TO -27 USING 3M EC-2216 ADHESIVE.

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-17</b>	REV <b>1</b>
MAT'L <b>REAR</b>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TREAT <b>FINISH</b>	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: <b>MACKOVJAK</b>	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: <b>CLOUGH</b>	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: <b>ANDERSON</b>	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: <b>LINDSAY</b>	USED ON MODEL
APPROVED: <b>GILBERT</b>	<b>H175</b>
SCALE <b>1:4</b>	DATE <b>5/27/2016</b>
SHEET 10 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-19)  
WELDMENT 2

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-19</b>	REV <b>1</b>
MAT'L HEAT TREAT FINISH POWDER COAT YELLOW SPEC FED #13538	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .010 FRACTIONS ± 1/8 .XX ± .03 ANGLES ± 1° .X ± .1 SURFACES = 125° ✓	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: <b>MACKOVJAK</b> CHECKED: <b>CLOUGH</b> OPPTS APPR: <b>ANDERSON</b> QA APPR: <b>LINDSAY</b> APPROVED: <b>GILBERT</b>	
USED ON MODEL <b>H175</b>	
SCALE <b>1:4</b>	DATE <b>5/27/2016</b>
SHEET 11 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-21)

CLAMP BEAM 1

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-21</b>	REV <b>1</b>
MAT'L A36/1018/1020 HR TREAT FINISH SEE -19 SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: <b>MACKOVJAK</b>	USED ON MODEL
CHECKED: <b>CLOUGH</b>	<b>H175</b>
OPPS APPR: <b>ANDERSON</b>	
QA APPR: <b>LINDSAY</b>	
APPROVED: <b>GILBERT</b>	
SCALE 1:3	DATE 5/27/2016
SHEET 12 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-23)

VERTICAL BEAM 2

<b>DART</b> AEROSPACE	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-23</b>	REV <b>1</b>
MAT'L STEEL TUBE	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125° ✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
SCALE 1:2	DATE 5/27/2016
	SHEET 13 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



(-25)





BRACE 3

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-25</b>	REV <b>1</b>
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH SEE -19	.XXX ± .010 FRACTIONS ± 1/8
SPEC	.XX ± .03 ANGLES ± 1°
	.X ± .1 SURFACES = 125°
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:2	DATE 5/27/2016
	SHEET 14 OF 20



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
APPROVED				



(27)




CLAMP BEAM 2

DART AEROSPACE			
TITLE RESCUE HOIST SLING			
DWG NO. RBEM259V1000102-27			REV 1
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		
HEAT TREAT	.XXX ± .005 FRACTIONS ± 1/8		
FINISH POWDER COAT YELLOW	.XX ± .01 ANGLES ± 5°		
SPEC FED #13538	.X ± .1 SURFACES = 125/		
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES .015 X 45° OR .015R		
CHECKED: CLOUGH	2. DIMENSIONAL LIMITS APPLY AFTER PLATING		
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009		
QA APPR: LINDSAY	USED ON MODEL		
APPROVED: GILBERT	H175		
SCALE 1:2	DATE 5/27/2016	SHEET 15 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED

2X .260 X .728 THRU ALL  
 .433  $\nabla$  .28




(-29)

ADJUSTABLE BUMPER

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-29</b>	REV <b>1</b>
MAT'L 6061	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH CLEAR ANODIZE	.XXX $\pm$ .005 FRACTIONS $\pm$ 1/8
SPEC MIL-A-8625F, TYPE II, CLASS I	.XX $\pm$ .01 ANGLES $\pm$ .5°
DRAWN BY: MACKOVJAK	.X $\pm$ .1 SURFACES = 125°
CHECKED: CLOUGH	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 1:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 5/27/2016	USED ON MODEL
SHEET 16 OF 20	H175

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






(-31)  
SWING BOLT

<b>DART</b> AEROSPACE	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-31</b>	REV <b>1</b>
MAT'L SS 303 TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: <b>MACKOVJAK</b> CHECKED: <b>CLOUGH</b> OPPTS APPR: <b>ANDERSON</b> QA APPR: <b>LINDSAY</b> APPROVED: <b>GILBERT</b>	
USED ON MODEL <b>H175</b>	
SCALE <b>1:1</b>	DATE <b>5/27/2016</b>
SHEET 17 OF 20	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS			
REV	ECR	DESCRIPTION	DATE
			INITIAL
			APPROVED






(33)

PAD 1

<b>DART AEROSPACE</b>	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-33</b>	REV <b>1</b>
MAT'L C200	UNLESS OTHERWISE SPECIFIED
HEAT	DIMENSIONS ARE IN INCHES
TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH	.XX ± .03 ANGLES ± 1°
SPEC	.X ± .1 SURFACES = 125° ✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:2	DATE 5/27/2016
	SHEET 18 OF 20

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS			
REV	ECR	DESCRIPTION	DATE
			INITIAL
			APPROVED





TITLE		RESCUE HOIST SLING	
DWG NO.		RBEM259V1000102-35	
REV		1	
MAT'L C200		UNLESS OTHERWISE SPECIFIED	
HEAT		DIMENSIONS ARE IN INCHES	
TREAT		XXX ± .010 FRACTIONS ± 1/8	
FINISH		.XX ± .03 ANGLES ± 1°	
SPEC		.X ± .1 SURFACES = 125°	
DRAWN BY: MACKOVJAK		1. BREAK ALL SHARP EDGES	
CHECKED: CLOUGH		.015 x 45° OR .015R	
OPPS APPR: ANDERSON		2. DIMENSIONAL LIMITS APPLY	
QA APPR: LINDSAY		AFTER PLATING	
APPROVED: GILBERT		3. INTERPRET DIM AND TOL PER	
SCALE		ASME Y14.5M-2009	
1:2		USED ON MODEL	
DATE		H175	
5/27/2016		SHEET 19 OF 20	

(-35)

PAD 2

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS			
REV	ECR	DESCRIPTION	DATE
			INITIAL
			APPROVED



SECTION A-A

(-37)

KNOB



<b>DART</b> AEROSPACE	
TITLE <b>RESCUE HOIST SLING</b>	
DWG NO. <b>RBEM259V1000102-37</b>	REV <b>1</b>
MAT'L ALUMINUM	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH	.XXX ± .005 FRACTIONS ± 1/8
SPEC	.XX ± .01 ANGLES ± .5°
	.X ± .1 SURFACES = 125° ✓
DRAWN BY: MACKOVJAK	1. BREAK ALL SHARP EDGES
CHECKED: CLOUGH	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: GILBERT	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	H175
SCALE 1:1	DATE 5/27/2016
	SHEET 20 OF 20